

## MEGA DUO OVAL MEGA DUO OVAL WITH MOULDED PANEL


- bathing with a friend: two identical back rests and centrally positioned waste
- wide arm rests on both sides provide optimum bathing comfort
- made of Kaldewei steel enamel 3.5 mm
- the moulded panel emphasises the high design standard and enables the bath to be free-standing

















Similar illustration

External width     b     900     900 mm       Depth     c     450     450 mm       External length (bottom)     a_1     -     1380 mm       External width (bottom)     b_1     -     540 mm       Overall heigth with panel     c_1     540 mm     580 mm       Overall heigth (bottom)     d     1680 mm     1680 mm       Internal length (bottom)     d     1680 mm     1680 mm       Internal length (bottom)     g     360 mm     1290 mm       Internal width (bottom)     g     360 mm     360 mm       Distance top edge to centre of overflow hole     j     70 mm       Distance top edge to	Model No.		184	184-7
Depthc450450 mmExternal length (bottom)a,-1380 mmExternal length (bottom)b,-540 mmOveral height with panelc,-580 mmInternal length (top)d16801680Internal length (top)e2290 mm1290 mmInternal length (top)f, f, f_2780; 640 mm780; 640 mmInternal width (top)g360 mm360 mmHeight with feeth565 600 mm360 mmHeight of rimi565 600 mm565 600 mmDistance top edge to centre of overflow holej70 mmDistance top edge to centre of overflow holej70 mmDistance top edge to centre of footn450 mmDistance between the feeto820 mmMax width of feetp480 mmWidt of rim (foot end; lengthwise)si, s <sub>2</sub> , s <sub>3</sub> 60; 60; 130 mmDistance between centre holesu310 mmArmerst depthv140140 mmWeight of the enamelled batht to in kg-55 mmWeigh	External length	а	1800	1800 mm
External length (bottom)     a.     -     1380 mm       External width (bottom)     b.     -     540 mm       Overall height with panel     c.     580 mm       Internal length (bottom)     d     1680     1680 mm       Internal length (bottom)     d     1680 mm     1680 mm       Internal length (bottom)     e     1290 mm     1290 mm       Internal width (bottom)     f, f, f.     780; 640 mm     1680 mm       Internal width (bottom)     g     360 mm     360 mm       Internal width (bottom)     g     556 fo0 mm     565 fo0 mm       Internal width feet     h     565 fo0 mm     50 mm       Distance top degle to centre of drain hole     k     900     900 mm       Distance four end frain hole     n     480 mm     480 mm	External width	b	900	900 mm
External width (bottom) $b_1$ -540 mmOverall height with panel $c_1$ 580 mmInternal length (top)d16801680Internal length (bottom)e1290 mmInternal width (top) $f_1; f_2$ 780; 640Internal width (bottom)g360360 nmInternal width (bottom)g565: 600 mmInternal width (bottom)g565: 600 mmInternal width (bottom)j700 mmDistance top edge to centre of overflow holej700 mmDistance top edge to centre of drain holek900Diameter of overflow hole152Distance top edge to centre of footn490Distance between the feet0360 mmDistance between the feet0820 mmDistance between the feet0360 mmDistance between the feet0360 mmDistance between the feet0300 mmDistance between the feet0300 mmDistance between the feet0310 mmDistance between the feet1140 mmWidth of rim (foot end; lengthwise)186186Vatre volume** in litres186186Weight of the enamelled bath tub in kg556Anti-slip $\mathcal{O}$ 435 mm $\mathcal{O}$ 435 mm	Depth	с	450	450 mm
Overall height with panel $c_1$ $-$ 580 mmInternal length (top)d16801680mmInternal length (bottom)e12901290 mmInternal length (bottom)f <sub>1</sub> ; f <sub>2</sub> 780; 640mmInternal width (top)f <sub>1</sub> ; f <sub>2</sub> 780; 640780; 640 mmInternal width (top)g360360 mmHeight of rimg360365 600 mmHeight of rimi5050 mmDistance top edge to centre of overflow holej7070 mmDistance top edge to centre of drain holek900900 mmDiameter of overflow holei5252 mmDistance top edge to centre of footn490490 mmDistance top edge to centre of footn490490 mmDistance top edge to centre of footn48060; 60; 130 mmDistance top edge to centre of footn310 mm310 mmDistance between the feet0310 mm310 mmDistance between centre holesu310 mm310 mmMitch of rim (foot end; lengthwise)s <sub>1</sub> ; s <sub>2</sub> : s <sub>3</sub> 60; 60; 130310 mmDistance between the feetv140140 mmWidth of rim (foot end; lengthwise)s186186Weight of the enamelled bath tub in kg55Anti-slip $\mathcal{O}$ 435 mm $\mathcal{O}$ 435 mm $\mathcal{O}$	External length (bottom)	a1	-	1380 mm
Internal length (top)     d     1680 <th1680< th="">     1600     1600<td>External width (bottom)</td><td>b<sub>1</sub></td><td>-</td><td>540 mm</td></th1680<>	External width (bottom)	b <sub>1</sub>	-	540 mm
Internal leght (bottom)e12901290 mmInternal width (top)f_1; f_2780; 640 mmInternal width (bottom)g360360 mmInternal width (bottom)g360360 mmHeight with feeth565-600565-600 mmHeight of rimi5050 mmDistance top edge to centre of overflow holej7070 mmDistance tup edge to centre of drain holek900900 mmDiameter of overflow hole15252 mmDiameter of overflow holen5252 mmDiameter of drain holen490490 mmDistance tup edge to centre of footn490490 mmDistance foot end of tub edge to centre of footn490480 mmDistance between the feetp480480 mmWidth of rim (foot end; lengthwise)s1; s2; s360; 60; 130 mm60; 60; 130 mmDistance between centre holesu310 mm310 mmAmmest depthv140140 mm140 mmWeight of the enamelled bath tub in kg55Anti-slip04350435 mm0435 mm	Overall height with panel	C1	-	580 mm
Internal width (top) $f_i; f_2$ 780; 640 mmInternal width (bottom)g360360 mmInternal width (bottom)g360360 mmHeight with feeth565-600565-600 mmHeight of rimi5050 mmDistance top edge to centre of overflow holej7070 mmDistance tub edge to centre of drain holek900900 mmDiameter of overflow hole15252 mmDiameter of drain holem5252 mmDistance tub edge to centre of footn490490 mmDistance between the feet0820820 mmMax. width of feetp480480 mmWidth of rim (foot end; lengthwise) $\mathbf{s}_i; \mathbf{s}_2, \mathbf{s}_3$ 60; 60; 130Distance between centre holesu310310 mmArmest depthv140140 mmWater volume** in litres186186Weight of the enamelled bath tub in kg55-Arti-slip $\emptyset$ 435 mm $\emptyset$ 435 mm	Internal length (top)	d	1680	1680 mm
Internal width (bottom)     g     360     360 mm       Height with feet     h     565-600 mm     565-600 mm       Height of rim     i     50     50 mm       Distance top edge to centre of overflow hole     j     70     70 mm       Distance tub edge to centre of drain hole     k     900     900 mm       Diameter of overflow hole     i     52     52 mm       Diameter of drain hole     m     52     52 mm       Diameter of drain hole     m     52     52 mm       Diameter of drain hole     m     490     490 mm       Distance between the feet     o     820 mm     820 mm       Max. width of feet     p     480     480 mm       Width of rim (foot end; lengthwise)     s <sub>1</sub> ; s <sub>2</sub> , s <sub>3</sub> 60; 60; 130     60; 60; 130 mm       Distance between centre holes     u     310     310 mm       Armrest depth     v     140     140 mm       Weight of the enamelled bath tub in kg     5     -       Weight of the enamelled bath tub in kg     55     - <td< td=""><td>Internal length (bottom)</td><td>е</td><td>1290</td><td>1290 mm</td></td<>	Internal length (bottom)	е	1290	1290 mm
Height with feet     h     565-600     565-600     m       Height of rim     i     50     50     mm       Distance top edge to centre of overflow hole     j     70     70     mm       Distance tub edge to centre of drain hole     k     900     900     mm       Diameter of overflow hole     i     52     52     mm       Diameter of drain hole     m     52     52     mm       Distance foot end of tub edge to centre of foot     n     52     52     mm       Distance foot end of tub edge to centre of foot     n     490     490     mm       Distance between the feet     o     820     820     mm       Max. width of fiet     p     480     480     mm       Distance between centre holes     u     310     310     mm       Distance between centre holes     u     310     310     mm       Atter volume** in littes     u     160     160     160     160       Weight of the enamelled bath tub in kg     T     5	Internal width (top)	f <sub>1</sub> ; f <sub>2</sub>	780; 640	780; 640 mm
Height of rim     i     50     50 mm       Distance top edge to centre of overflow hole     j     70     70 mm       Distance tub edge to centre of drain hole     k     900     900 mm       Diameter of overflow hole     I     52     52 mm       Diameter of drain hole     m     52     52 mm       Diameter of drain hole     n     490     490 mm       Distance foot end of tub edge to centre of foot     n     490     490 mm       Distance between the feet     0     820     820 mm       Max. width of feet     p     480     480 mm       Width of rim (foot end; lengthwise)     s <sub>1</sub> ; s <sub>2</sub> , s <sub>3</sub> 60; 60; 130     60; 60; 130 mm       Distance between centre holes     u     310     310 mm       Armrest depth     v     140     140 mm       Water volume** in litres     186     186       Weight of the enamelled bath tub in kg     55     -       Arti-slip     Ø 435 mm     Ø 435 mm	Internal width (bottom)	g	360	360 mm
Distance top edge to centre of overflow hole     j     70     70     70       Distance tub edge to centre of drain hole     k     900     900 mm       Diameter of overflow hole     I     52     52 mm       Diameter of drain hole     m     52     52 mm       Diameter of drain hole     m     52     52 mm       Distance foot end of tub edge to centre of foot     n     490     490 mm       Distance between the feet     o     820     820 mm       Max. width of feet     p     480     480 mm       Width of rim (foot end; lengthwise)     s <sub>1</sub> ; s <sub>2</sub> ; s <sub>3</sub> 60; 60; 130     60; 60; 130 mm       Distance between centre holes     u     310     310 mm       Armrest depth     v     140     140 mm       Water volume** in litres     55     -       Weight of the enamelled bath tub in kg     55     -       Arti-slip     Ø 435 mm     Ø 435 mm	Height with feet	h	565-600	565-600 mm
Distance tub edge to centre of drain holek900900 mmDiameter of overflow holeI5252 mmDiameter of overflow holem5252 mmDiameter of drain holem5252 mmDistance foot end of tub edge to centre of footn490490 mmDistance between the feeto820820 mmMax. width of feetp480480 mmWidth of rim (foot end; lengthwise)s1; s2; s360; 60; 13060; 60; 130 mmDistance between centre holesu310310 mmArmrest depthv140140 mmWater volume** in litres55-Meight of the enamelled bath tub in kg55-Anti-slip $\emptyset$ 435 mm	Height of rim	i	50	50 mm
Diameter of overflow hole     I     52     52 mm       Diameter of overflow hole     m     52     52 mm       Diameter of drain hole     m     52     52 mm       Distance foot end of tub edge to centre of foot     n     490     490 mm       Distance between the feet     o     820     820 mm       Max. width of feet     p     480     480 mm       Width of rim (foot end; lengthwise)     s <sub>1</sub> ; s <sub>2</sub> ; s <sub>3</sub> 60; 60; 130     60; 60; 130 mm       Distance between centre holes     u     310     310 mm       Armrest depth     v     140     140 mm       Water volume** in litres     55     -       Weight of the enamelled bath tub in kg     55     -       Anti-slip     Ø 435 mm     Ø 435 mm	Distance top edge to centre of overflow hole	j	70	70 mm
Diameter of drain holem5252 mmDistance foot end of tub edge to centre of footn490490 mmDistance between the feeto820820 mmMax. width of feetp480480 mmWidth of rim (foot end; lengthwise)s <sub>1</sub> ; s <sub>2</sub> ; s <sub>3</sub> 60; 60; 13060; 60; 130 mmDistance between centre holesu310310 mmArmrest depthv140140 mmWater volume** in litres55-Mati-slip0 4350 435 mm	Distance tub edge to centre of drain hole	k	900	900 mm
Distance foot end of tub edge to centre of footn490490 mmDistance between the feeto820820 mmMax. width of feetp480480 mmWidth of rim (foot end; lengthwise) $s_1; s_2; s_3$ 60; 60; 13060; 60; 130 mmDistance between centre holesu310310 mmArmrest depthv140140 mmWater volume** in litres5-Anti-slip $\emptyset$ 435 mm	Diameter of overflow hole	I	52	52 mm
Distance between the feet     o     820     820 mm       Max. width of feet     p     480     480 mm       Width of rim (foot end; lengthwise)     s1; s2; s3     60; 60; 130     60; 60; 130 mm       Distance between centre holes     u     310     310 mm       Armrest depth     v     140     140 mm       Water volume** in litres     55     -       Anti-slip     Ø 435 mm	Diameter of drain hole	m	52	52 mm
Max. width of feet     p     480     480 mm       Width of rim (foot end; lengthwise)     s1; s2; s3     60; 60; 130     60; 60; 130 mm       Distance between centre holes     u     310     310 mm       Armrest depth     v     140     140 mm       Water volume** in litres     186     186       Weight of the enamelled bath tub in kg     55     -       Anti-slip     Ø 435 mm	Distance foot end of tub edge to centre of foot	n	490	490 mm
Width of rim (foot end; lengthwise) s1; s2; s3 60; 60; 130 60; 60; 130 mm   Distance between centre holes u 310 310 mm   Armrest depth v 140 140 mm   Water volume** in litres 186 186   Weight of the enamelled bath tub in kg 55 -   Anti-slip Ø 435 Ø 435 mm	Distance between the feet	0	820	820 mm
Distance between centre holes u 310 310 mm   Armrest depth v 140 140 mm   Water volume** in litres 186 186   Weight of the enamelled bath tub in kg 55 -   Anti-slip Ø 435 Ø 435 mm	Max. width of feet	р	480	480 mm
Armrest depthv140140 mmWater volume** in litres186186Weight of the enamelled bath tub in kg55-Anti-slip0 4350 435 mm	Width of rim (foot end; lengthwise)	s <sub>1</sub> ; s <sub>2;</sub> s <sub>3</sub>	60; 60; 130	60; 60; 130 mm
Water volume** in litres     186     186       Weight of the enamelled bath tub in kg     55     -       Anti-slip     Ø 435     Ø 435 mm	Distance between centre holes	u	310	310 mm
Weight of the enamelled bath tub in kg     55     -       Anti-slip     Ø 435     Ø 435 mm	Armrest depth	V	140	140 mm
Anti-slip Ø 435 Ø 435 mm	Water volume** in litres		186	186
	Weight of the enamelled bath tub in kg		55	-
Full anti-slip 900 x 300 900 x 300 mm	Anti-slip		Ø 435	Ø 435 mm
	Full anti-slip		900 x 300	900 x 300 mm

